

# Fast and energy saving

TDR 8 Programmable eco

**The Turbo Deli Rotisserie is the fastest original rotisserie in the industry. The TDR's cavity is fed with air, cooking a rotisserie chicken as it is meant to be: crispy and delicious while maintaining an attractive appearance for hours.**

The TDR pushes the air throughout the cavity, resulting in an improved heat transfer on the products and consequently in a reduced electricity consumption during the preparation process.

Thanks to Eco Cooking the TDR saves an additional 5% on energy. Add to this the improved heat transfer on the products and a fast preparation process and you have yourself the most energy-efficient rotisserie with a high output.

Cook Correction corrects alterations in the cooking cycle that are due to half-loads, overloads, or products with a difference in temperature. It measures abnormalities in the temperature curve and corrects the cycle automatically, ensuring food-safety and energy-efficient cooking.



Programmable controls



Large product view



## Features TDR 8 Programmable

### Top features

- Controls with manual settings
- Easy to operate - set time, temperature and start the rotisserie
- Endless possibilities: poultry (parts), pork roast, ribs, lamb, roast beef, pork belly, meat loaf, porchetta and other proteins

### Standard characteristics


- 8 Meat fork, V-spit, basket or rack positions
- Rotor for up to 40 chickens (1,2 kg)
- Range of accessories available for preparation of chicken, chicken parts, ribs, etc.

### Accessories

- Meat forks (included)
- Multi-purpose baskets
- V-spits
- Chicken racks
- Matching stand

### Optional

- Stacked unit
- Pass-through
- Ventless hood



Ventless hood (optional)



Stacked TDR

## TDR 8 Programmable

- 1 Power cable 2.2 m
- 2 Exhaust opening
- 3 Space to the wall
- 4 Location for socket

### Dimensions TDR 8

|                  |         |
|------------------|---------|
| Width            | 995 mm  |
| Depth            | 830 mm  |
| Depth with hood  | 970 mm  |
| Height           | 1065 mm |
| Height on stand  | 1796 mm |
| Height with hood | 1395 mm |

### Technical data TDR 8

|              |               |
|--------------|---------------|
| Net weight   | 185 kg        |
| Gross weight | 216 kg        |
| Voltage      | 3N~ 400/230 V |
| Frequency    | 50/60 Hz      |
| Power        | 10.5 kW       |

### Dimensions TDR 8+8

|                  |         |
|------------------|---------|
| Width            | 995 mm  |
| Depth            | 830 mm  |
| Depth with hood  | 970 mm  |
| Height           | 2095 mm |
| Height with hood | 2344 mm |

### Technical data TDR 8+8

|              |               |
|--------------|---------------|
| Net weight   | 375 kg        |
| Gross weight | 435 kg        |
| Voltage      | 3N~ 400/230 V |
| Frequency    | 50/60 Hz      |
| Power        | 21 kW         |

Specifications and technical data are subject to amendment without prior notice.

These are basic drawings. For more detailed technical information, please refer to the installation manual at [www.frijado.com](http://www.frijado.com).

