

Optima | 8 | 5 | 0

Product data sheet – Electric infra chip scuttle

MKN-No.:
2020601

Food warming appliance for use in commercial kitchens and food distribution.



Technical highlights

Material:

Casing and cover are made completely of CNS (material No. 1.4301) / AISI 304.
Visible surfaces with polished and satin finish, 320 grit.

Bendings:

Cover bent downwards 50 mm at the front and on the sides, bent upwards 25 mm at the rear. Designed as a drip edge at the front on the bottom side. 50 mm cover projection closed to the appliance body. With tightly welded drain channels on the side – rounded (R30) at the rear.

Body:

Buckling resistant, self-supporting, closed construction with side walls, rear wall and bottom.

Control panel:

Control panel with profile to protect the control elements, can be taken off at the front for simple and cost-efficient service access. Embossing behind the control knobs, ergonomiacally shaped knobs for a easy identification of the position.

Effective area:

Deep drawn basin completely of CNS (1.4301) (AISI 304) welded seamlessly and greaseproof. With large radii for easy cleaning.

Installation:

Equipped for installation of appliance feet which are adjustable in height (optional) or for installation on a plinth provided by customer.

Type of energy:

Appliance is completely wired internally for the electrical supply provided by customer. All contactors required for operation are installed.

Special feature:

Heating:

Heating by ceramic radiant heating elements, activated via the appliance switch.



Product data sheet — Electric infra chip scuttle

MKN-No.:
2020601

Food warming appliance for use in commercial kitchens and food distribution.

Current drawings you will find here:
www.mkn.com
▶ Partner Login
▶ spare parts database & download

Further features

- connection, sealing by special clip bars flush mounted to the cover (optional)
- removable insert containers GN 1/1 with perforated shelf for large capacities and for keeping hot in a dry condition

Technical data

Dimensions (LxWxH*) (mm):	400 x 850 x 700
Effective area:	1
Dim.: effect. area (LxWxH) (mm):	325 x 530 x 200
Diameter (mm):	
Nominal capacity (L):	
Nominal fill quantity (L):	
Connected load (electrical) (kW):	1
Voltage ¹ (V):	230 1 NPE AC
Recommended fuses (A):	1 x 16
Frequency range (Hz):	50/60
Rated heat load (kW):	
Standard gas pressure – natural gas ² (mbar):	
Standard gas pressure – liquid gas ² (mbar):	
Heat-up time (Min.):	
Vapour pressure (bar):	
Refrigeration capacity (kW):	
Net weight (kg):	48
Gross weight ³ (kg):	55
Heat emission latent (W):	175
Heat emission sensitive (W):	700
Type of protection:	IPX5

* Carcass height plus optional appliance feet with a height of 150 mm or 200 mm

Product safety

- CE mark

Installation requirements

- electrical supply provided by customer

Option / accessories

MKN-No.:	Description:
10017300	scoop for french fries
845031	wing door for an appliance length of 400 mm
10020516	hygiene insert R20 (H2) for cabinet 400 mm

¹ special voltages on request
³ seaworthy packing on request

² further types of gas on request

